Watch video: https://youtu.be/Fel2WrnFgjc?t=48m38s

Topics List

- Conceptual Database Design
- Build conceptual data model
- Worked Example

- The process of constructing a model of the data used in an enterprise, independent of all physical considerations.
- The goal of this phase is to produce a conceptual schema (which includes identification of the important entity types, relationship types, and attributes) for the database that is independent of a specific DBMS. We will use ER modelling during this phase.

Overview Database Design Methodology

- Step 1 Build conceptual data model.
- Step 2 Build and validate logical data model.
- Step 3 Translate logical data model for target DBMS.
- Step 4 Design file organisations and indexes.
- Step 5 Design user views.
- Step 6 Design security mechanisms.
- Step 7 Consider the introduction of controlled redundancy.
- Step 8 Monitor and tune the operational system.

Build conceptual data model

- Step 1.1 Identify entity types.
- Step 1.2 Identify relationship types.
 - 1.2.1 Cardinality.
 - 1.2.2 Participation.
- Step 1.3 Identify and associate attributes with entity or relationship types.
- Step 1.4 Determine attribute domains.
- Step 1.5 Determine candidate, primary, and alternate key attributes.
- Step 1.6 Consider use of enhanced modelling concepts (optional step).
- Step 1.7 Check model for redundancy.
- Step 1.8 Validate conceptual model against user transactions.
- Step 1.9 Review conceptual data model with user.

Topics List

- Conceptual Database Design
- Build conceptual data model
- Worked Example

Build conceptual data model Identify entity types

- One method is to examine the users' requirements specification for nouns or noun phrases.
- Also look for major objects such as people, places, or concepts of interest, excluding those nouns that are merely qualities of other objects.
- Document the entity types.

Identify relationship types

- This is a key step in the process of building a conceptual data model.
 - One method is to examine users' requirements specification for verbs or verbal expressions. For example, if we have identified 2 entity types as Staff and PropertyForRent, a possible expression in the requirements specification would be: Staff Manages PropertyForRent.
 - Use entity—relationship (ER) modelling to understand the relationship types.
 - Determine the multiplicity constraints of relationships.
 These are used to check and maintain data quality.
 - Document the relationship types.

Identify and associate attributes with entity or relationship types.

- Attributes can be identified where noun or noun phrase is a property, quality, identifier, or characteristic of one of the entity or relationship types previously found.
- Identify whether attributes are:
 - Simple/composite
 - Single/multi-valued
 - Derived
- Document the attributes.

Documenting attributes

- Record the following information for each attribute:
 - attribute name and description;
 - data type and length;
 - any aliases that the attribute is known by;
 - whether the attribute must always be specified (in other words, whether the attribute allows or disallows nulls);
 - whether the attribute is multi-valued;
 - whether the attribute is composite, and if so, which simple attributes make up the composite attribute;
 - whether the attribute is derived and, if so, how it should be computed;
 - default values for the attribute (if specified).

Determine attribute domains

- A domain is a pool of values from which one or more attributes draw their values.
- A domain specifies:
 - allowable set of values for the attribute;
 - size and format of the attribute.
- Document the attribute domains.

Guidelines for choosing a primary key

- Select the candidate key
 - with the minimal set of attributes;
 - that is less likely to have its values changed;
 - that is less likely to lose uniqueness in the future;
 - with fewest characters (for those with textual attribute(s));
 - with the smallest maximum value (for numerical attributes);
 - that is easiest to use from the users' point of view.

Topics List

- Conceptual Database Design
- Build conceptual data model
- Worked Example

 You have been asked to design a database for a garage. The manager of the garage has told you details (on next 2 slides).

To do:

 Produce an Entity Relationship diagram to clarify your understanding of the client's requirements.

- We keep a list of customers who book in repair jobs. Their customerld, name (fName, IName), address (street, town and county) and contact number are recorded.
- For each repair job, we allocate a new job number, record the date and vehicle registration number.
- We keep a list of all our mechanics, with their hourly rate of pay. We also record their staffld, and name (fName, IName).
- We keep a list of the different parts that we use. For each part
 we record a part number, description, quantity in stock and
 cost of the part.
- We record the supplier details for the supplier who supplies each part. These details include supplier number, supplier name (fName, IName), address (street, town and county), contact number, fax number and email address.

- Each customer will submit 0 or more repair jobs. Each repair job involves one and only one customer.
- There is only one supplier for each particular part and each supplier will supply 0 or more parts.
- Every repair job is worked on by at least one mechanic and each mechanic will work on 0 or more repair jobs.
 For billing purposes, we need to keep track of all the time that each mechanic spends on a given job.
- A repair job will use 0 or more parts and a part can be used in 0 or more repair jobs. We need to keep track of the quantity of the part used in each repair job.

Step 1.1 Identify entities

Step 1.1 Identify entities

- Customer
- Repair Job
- Mechanic
- Part
- Supplier


Step 1.2 Identify relationships

Step 1.2 Identify relationships

- Each customer will submit 0 or more repair jobs.
 Each repair job involves one and only one customer.
 - Customer 1..1 submits 0..* Repair Job
- There is only one supplier for each particular part and each supplier will supply 0 or more parts.
 - Supplier 1..1 supplies 0..* Part

Step 1.2 Identify relationships

- Every repair job is worked on by at least one mechanic and each mechanic will work on 0 or more repair jobs.
 - Mechanic 1..* worksOn 0..* Repair Job
- A repair job will use 0 or more parts and a part can be used in 0 or more repair jobs.
 - Repair Job 0..* uses 0..* Part



Step 1.3 Identify and associate attributes with entities or relationships

- Entity Type attributes:
 - Customer:customerId, name (fName, IName), address (street, town, county), contactNumber
 - Repair Job: jobNumber, jobDate, regNumber
 - Mechanic: staffld, name (fName, IName), hourlyRate
 - Supplier: supplierNumber, supplierName (fName, IName), address (street, town, county), contactNumber, faxNumber, emailAddress
 - Part: partNumber, description, stockQuantity, partCost

Step 1.3 Identify and associate attributes with entities or relationships

Relationship Type attributes:

• There is a requirement to record the time that each Mechanic spends on a given Repair Job. This attribute time is not an attribute of Mechanic because there would be multiple time values for each Repair Job that the Mechanic works on. Likewise, it is not an attribute of Repair Job because there would be multiple time values for each Mechanic working on the Repair Job. It represents the amount of time one Mechanic works on one Repair Job. So for each relationship occurrence between Mechanic and Repair Job there will be a time value.

Step 1.3 Identify and associate attributes with entities or relationships

Relationship Type attributes:


• There is also a requirement to record the quantity of a Part used in each Repair Job. This attribute quantity is not an attribute of Part because there would be multiple quantity values for each Repair Job that the Part is used in. Likewise, it is not an attribute of Repair Job because there would be multiple quantity values for each Part being used in the Repair Job. It represents the quantity amount of one Part being used in one Repair Job. So for each relationship occurrence between Part and Repair Job there will be a quantity value.

Step 1.4 Determine attribute domains

 In the data dictionary record the allowable set of values for the attribute; and the size and format of the attribute.

- Step 1.5 Determine candidate, primary, and alternate key attributes
 - Customer: Candidate keys: customerld, name and address, contactNumber
 Primary key: customerld
 - Repair Job: Candidate key: jobNumber Primary key: jobNumber
 - Mechanic: Candidate key: staffld Primary key: staffld

- Step 1.5 Determine candidate, primary, and alternate key attributes
 - Supplier: Candidate keys: supplierNumber, supplierName and address, contactNumber, faxNumber, emailAddress
 Primary key: supplierNumber
 - Part: Candidate keys: partNumber, description
 Primary key: partNumber



Worked Example (Solution)

