

Game of Pong V9.0

Using Pythagoras Theorem for Collision Detection

Produced Dr. Siobhán Drohan
by: Mr. Colm Dunphy
 Mr. Diarmuid O'Connor



Waterford Institute *of* Technology
INSTITIÚID TEICNEOLAÍOCHTA PHORT LÁIRGE

Department of Computing and Mathematics
<http://www.wit.ie/>

We introduced a
'Simple' Collision Detection Algorithm
in PongGameV3_0.

Now we will look
at a more complex, versatile algorithm,
using Pythagoras Theorem!

'Simple' Collision Detection Algorithm

Method signature:

boolean hitPaddle (Paddle paddle, Ball ball)

Algorithm:



- 1) **Measure** the size of the gap between the paddle and the ball.
- 2) If the ball is too far away from the Paddle on the **X axis** to have a collision
 → return false
- 3) If the ball is too far away from the Paddle on the **Y axis** to have a collision
 → return false
- 4) Otherwise
 → return true.

'Pythagoras' Collision Detection Algorithm


Method signature:

boolean hitPaddle (Paddle paddle, Ball ball)

- Two collision approaches:
 1. The ball overlaps the paddle straight on,
→ returns true.
 2. The ball overlaps the corner of the paddle,
→ returns true.
- Non collision
 - If the ball **does not overlap** the paddle,
→ return false



'Pythagoras' Collision Detection Algorithm



First we work out the distances

```
float circleDistanceX
```

```
= abs (ball.getXCoord() - paddle.getXCoord() - paddle.getPaddleWidth()/2);
```

```
float circleDistanceY
```

```
= abs (ball.getYCoord() - paddle.getYCoord() - paddle.getPaddleHeight()/2);
```

e.g. $\text{abs } (-5) = 5$

‘Pythagoras’ Collision Detection Algorithm

... the same code inside hitPaddle()

```
boolean hitPaddle (Paddle paddle, Ball ball)
{
    // These variables measure the magnitude of the gap
    // between the paddle and the ball.

    float circleDistanceX =
        abs(ball.getXCoord() - paddle.getXCoord() - paddle.getPaddleWidth()/2);


    float circleDistanceY =
        abs(ball.getYCoord() - paddle.getYCoord() - paddle.getPaddleHeight()/2);

    // code omitted...
}
```

1) COLLISIONS - STRAIGHT ON

'Pythagoras' Collision Detection Algorithm

- Ball & Paddle **not overlapping**



$$\text{circleDistanceX} = \text{abs}(300 - 530 - 35) = 265$$

$$\text{circleDistanceY} = \text{abs}(450 - 200 - 100) = 150$$


ball	
xCoord	300
yCoord	450
diameter	100

paddle	
xCoord	530
yCoord	200
paddleHeight	200
paddleWidth	70

```
float circleDistanceX = abs(ball.getXCoord() - paddle.getXCoord() - paddle.getPaddleWidth()/2);
float circleDistanceY = abs(ball.getYCoord() - paddle.getYCoord() - paddle.getPaddleHeight()/2);
```

'Pythagoras' Collision Detection Algorithm

- Ball & Paddle **not overlapping**



circleDistanceX = 265

circleDistanceY = 150

If $(265 > (35 + 50))$

→ returns from method with a **false**

i.e. ball and paddle have not made contact


ball	
xCoord	300
yCoord	450
diameter	100

paddle	
xCoord	530
yCoord	200
paddleHeight	200
paddleWidth	70

```
if (circleDistanceX > (paddle.getPaddleWidth()/2 + ball.getDiameter()/2)) { return false; }  
if (circleDistanceY > (paddle.getPaddleHeight()/2 + ball.getDiameter()/2)) { return false; }
```



'Pythagoras' Collision Detection Algorithm

- Ball & Paddle closer



circleDistanceX = abs(450 – 530 – 35) = 115


circleDistanceY = abs(300 - 200 - 100) = 0



```
float circleDistanceX = abs(ball.getXCoord() - paddle.getXCoord() - paddle.getPaddleWidth()/2);  
float circleDistanceY = abs(ball.getYCoord() - paddle.getYCoord() - paddle.getPaddleHeight()/2);
```

'Pythagoras' Collision Detection Algorithm

- Ball & Paddle closer



circleDistanceX = 115

circleDistanceY = 0

If (115 > (35 + 50))

→ returns from method with a **false**

i.e. ball and paddle have not made contact.


ball	
xCoord	450
yCoord	300
diameter	100

paddle	
xCoord	530
yCoord	200
paddleHeight	200
paddleWidth	70

```
if (circleDistanceX > (paddle.getPaddleWidth()/2 + ball.getDiameter()/2)) { return false; }  
if (circleDistanceY > (paddle.getPaddleHeight()/2 + ball.getDiameter()/2)) { return false; }
```

'Pythagoras' Collision Detection Algorithm

- Ball & Paddle **overlapping**



$$\text{circleDistanceX} = \text{abs}(481 - 530 - 35) = 84$$

$$\text{circleDistanceY} = \text{abs}(300 - 200 - 100) = 0$$


ball	
xCoord	481
yCoord	300
diameter	100

paddle	
xCoord	530
yCoord	200
paddleHeight	200
paddleWidth	70

```
float circleDistanceX = abs(ball.getXCoord() - paddle.getXCoord() - paddle.getPaddleWidth()/2);
float circleDistanceY = abs(ball.getYCoord() - paddle.getYCoord() - paddle.getPaddleHeight()/2);
```


'Pythagoras' Collision Detection Algorithm

- Ball & Paddle **overlapping**



circleDistanceX = 84
circleDistanceY = 0

- (1) if ($84 > (35 + 50)$) → boolean condition is false
- (2) if ($0 > (100 + 50)$) → boolean condition is false
- (3) if ($84 \leq (35)$) → boolean condition is false
- (4) If ($0 \leq 100$) → returns true



- (1) if ($\text{circleDistanceX} > (\text{paddle.getWidth()}/2 + \text{ball.getDiameter()}/2)$) { return false; }
- (2) if ($\text{circleDistanceY} > (\text{paddle.getHeight()}/2 + \text{ball.getDiameter()}/2)$) { return false; }
- (3) if ($\text{circleDistanceX} \leq (\text{paddle.getWidth()}/2)$) { return true; }
- (4) if ($\text{circleDistanceY} \leq (\text{paddle.getHeight()}/2)$) { return true; }

2) COLLISIONS - CORNERS


'Pythagoras' Collision Detection Algorithm

We will now look at the code when the ball hits a corner...

```
boolean hitPaddle (Paddle paddle, Ball ball)
{
    // code for ball and paddle overlapping straight on.
    // ...
    // Code for ball hitting the corner of the paddle.
    float cornerDistance =
        pow(circleDistanceX - paddle.getPaddleWidth()/2, 2) +
        pow(circleDistanceY - paddle.getPaddleHeight()/2, 2);

    if (cornerDistance <= pow(ball.getDiameter()/2, 2)){
        return true;
    }
    else{
        return false;
    }
}
```

Pythagoras Theorem



Pythagoras theorem:


The square of the **hypotenuse**
(the side opposite the right angle)

is equal to the sum of the squares
of the other two sides
(in this case x and y).

$$\text{hypotenuse}^2 = x^2 + y^2$$

'Pythagoras' Collision Detection Algorithm



As before we work out the distances



```
float circleDistanceX  
= abs(ball.getXCoord() - paddle.getXCoord() - paddle.getPaddleWidth()/2);
```

```
float circleDistanceY  
= abs(ball.getYCoord() - paddle.getYCoord() - paddle.getPaddleHeight()/2);
```

'Pythagoras' Collision Detection Algorithm



cornerDistance

is the square of the distance from the centre of the circle to the corner of the paddle.

float cornerDistance

```
= pow (circleDistanceX - paddle.getPaddleWidth()/2, 2) +  
pow (circleDistanceY - paddle.getPaddleHeight()/2, 2);
```

pow (num, toThePowerOf)

e.g. 5 squared = **pow** (5,2) = 25

'Pythagoras' Collision Detection Algorithm

- Ball hits the Paddle **corner**



ball	
xCoord	575
yCoord	194
diameter	20

paddle	
xCoord	580
yCoord	200
paddleHeight	100
paddleWidth	20

```
float circleDistanceX      575      - 580      - 20 / 2  
= abs (ball.getXCoord() - paddle.getXCoord() - paddle.getPaddleWidth()/2);  
= 15
```

```
float circleDistanceY      194      - 200      - 100 / 2  
= abs (ball.getYCoord() - paddle.getYCoord() - paddle.getPaddleHeight()/2);  
= 56
```

```
float cornerDistance      15      - 20/2  
= pow (circleDistanceX - paddle.getPaddleWidth()/2, 2) +  
  pow (circleDistanceY - paddle.getPaddleHeight()/2, 2);  
  
= pow (5,2) + pow(6,2) = 25 + 36 = 61
```

'Pythagoras' Collision Detection Algorithm

- Ball hits the Paddle **corner**



ball	
xCoord	575
yCoord	194
diameter	20

paddle	
xCoord	580
yCoord	200
paddleHeight	100
paddleWidth	20

61

pow (

20/2 , 2)

```
if (cornerDistance <= pow (ball.getDiameter()/2, 2)){  
    61     <= 100  
    return true;  
}  
else{  
    return false;  
}
```

hitPaddle (paddle, ball) method

```
boolean hitPaddle (Paddle paddle, Ball ball)
{
    // 1. Work out circleDistanceX and circleDistanceY
    float circleDistanceX = abs(ball.getXCoord() - paddle.getXCoord() - paddle.getPaddleWidth()/2);
    float circleDistanceY = abs(ball.getYCoord() - paddle.getYCoord() - paddle.getPaddleHeight()/2);

    // 2. Four straight on tests
    if (circleDistanceX > (paddle.getPaddleWidth()/2 + ball.getDiameter()/2)) { return false; }
    if (circleDistanceY > (paddle.getPaddleHeight()/2 + ball.getDiameter()/2)) { return false; }

    if (circleDistanceX <= (paddle.getPaddleWidth()/2)) { return true; }
    if (circleDistanceY <= (paddle.getPaddleHeight()/2)) { return true; }

    // 3. Corner calculation & test
    float cornerDistance = pow(circleDistanceX - paddle.getPaddleWidth()/2, 2) +
                           pow(circleDistanceY - paddle.getPaddleHeight()/2, 2);

    if (cornerDistance <= pow(ball.getDiameter()/2, 2))
        return true;
    else
        return false;
}
```

hitPaddle (paddle, ball) method

- In the **draw()** method,
the call to **hitPaddle(ball, paddle)** method
has no changes to it i.e. :

```
//If the player still has a life left in the current game,
//draw the ball at its new location and check for a collision with the paddle
if (livesLost < maxLivesPerGame){
    ball.display();
    //if ball and paddle are overlapping, Set variable to true, false if not
    boolean collision = hitPaddle(paddle, ball);
    if (collision == true){
        ball.hit();      //the ball is hit i.e. reverses direction.
        score++;        //increase the score in the current game by 1, if the player hit the
ball.
    }
}
```

Questions?



References

- Reas, C. & Fry, B. (2014) Processing – A Programming Handbook for Visual Designers and Artists, 2nd Edition, MIT Press, London.